

CERTIFICATE OF COMPLIANCE

Certificate Number 20140918-E79070
Report Reference E79070-19850130
Issue Date 2014-SEPTEMBER-18

Issued to: TOPWORX INC
3300 FERN VALLEY RD
LOUISVILLE KY 40213

**This is to certify that
representative samples of**

AUXILIARY DEVICES FOR USE IN HAZARDOUS
LOCATIONS and AUXILIARY DEVICES FOR USE IN
ZONE CLASSIFIED HAZARDOUS LOCATIONS
CERTIFIED FOR CANADA

See Addendum page for models


Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 1203, Explosion-Proof and Dust-Ignition-Proof Electrical
Equipment for Use in Hazardous (Classified) Locations;
UL 50E, Enclosures for Electrical Equipment, Environmental
Considerations;
CSA C22.2 No. 30-M1986, Explosion-proof enclosures for
use in Class I Hazardous Locations;
CSA C22.2 No. 25-1966, Enclosures for use in Class II
Groups E, F, and G Hazardous Location;
CSA-C22.2 NO. 60079-0:11, Explosive Atmospheres - Part 0:
Equipment - General Requirements;
CSA-C22.2 NO. 60079-11:14, Explosive Atmospheres - Part
11: Equipment Protection by Intrinsic Safety "i"

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada. The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers:  the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20140918-E79070
Report Reference E79070-19850130
Issue Date 2014-SEPTEMBER-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

US Listed Only:

Proximity switches for use in Class I, Groups A, B, C and D; Class II, Groups E, F and G; and Class III hazardous locations.

Model 81 followed by 1 or 2; followed 0; followed by 1 or 5; followed by 2 or 4; followed by 3; followed by letters and/or numbers.

Model 31 followed by 1; followed by 7; followed by 5; followed by 2 or 4; followed by 3; followed by letters and/or numbers.

Proximity switches for use in Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G; and Class III hazardous locations.

Model 81 followed by 1 or 2; followed 0; followed by 1 or 5; followed by 2 or 4; followed by 5; followed by letters and/or numbers.

Model 31 followed by 1; followed by 7; followed by 5; followed by 2 or 4; followed by 5; followed by letters and/or numbers.


William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20140918-E79070
Report Reference E79070-19850130
Issue Date 2014-SEPTEMBER-18

Canadian Listed Only:

Proximity switches for use in Class I, Groups A, B, C and D; Class II, Groups E, F and G; and Class III hazardous locations.

Model 81 followed by 1 or 2; followed 0; followed by 1 or 5; followed by 2 or 4; followed by 4; followed by letters and/or numbers.

Model 31 followed by 1; followed by 7; followed by 5; followed by 2 or 4; followed by 4; followed by letters and/or numbers.

Proximity switches for use in Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G; and Class III hazardous locations.

Model 81 followed by 1 or 2; followed 0; followed by 1 or 5; followed by 2 or 4; followed by 6; followed by letters and/or numbers.

Model 31 followed by 1; followed by 7; followed by 5; followed by 2 or 4; followed by 6; followed by letters and/or numbers.

Proximity switches for use in Class I, Zone 0, Ex ia IIC; Ex ia IIIC Hazardous Locations.

Model 81 followed by 1 or 2; followed 0; followed by 1 or 5; followed by 1, 2, 3, or 4; followed by F, G, or H, followed by letters and/or numbers, followed by Z. Intrinsically safe when connected in accordance with control drawing no. ES-04728-1.

Model 31 followed by 1; followed by 7; followed by 5; followed by 2 or 4; followed by F, G, or H, followed by letters and/or numbers, followed by Z. Intrinsically safe when connected in accordance with control drawing no. ES-04728-1.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

