

CAROM improves steam transport and distribution network and saves 200,000 Euros per year using Rosemount® Vortex flowmeters

RESULTS

- Steam transport and distribution improved by 3%
- Fuel savings of more than €200,000 per year
- Total investment recovered in just 25 days of operation
- Maintenance needs reduced by 300 man hours per year



APPLICATION

Thermal boilers for the production of superheated steam used in all the production units. Steam is transported to the petrochemical plants using a 3.5 km pipe network.

CUSTOMER

CAROM, which is a branch of Energy Bio Chemicals, is located in Onesti, Romania. Carom is a multi-purpose industrial petrochemical (butadiene, MTBE, LPG Synthetic rubber) plant. It comprises production and storage facilities, and a fully equipped and operational terminal for the storage and distribution of road bitumen. The site also has a transportation infrastructure for petroleum and petrochemical based products.

CHALLENGE

CAROM has nine thermal boilers for the supply of steam to the butadiene, MTBE fuel additive and synthetic rubber production units. Product quality and composition depend on the boilers delivering steam at a constant pressure.

The flow of superheated steam was being measured using three orifice plate flowmeters but these devices suffered a number of leakage problems in the pulse lines. Each meter needed a minimum of ten hours per week maintenance during winter and a minimum of two hours maintenance per week in summer. On average, the three meters were receiving a total of around 300 hours of maintenance each year.

Although the process could continue while the instruments were being maintained, valuable measurement data was lost during this time. In addition, the leakages were causing steam losses, which added to costs and presented a safety risk to workers.

"Emerson's Vortex technology enabled me to become a true Energy Manager and bring added value to my company."

Marian Stancu

Energy Chief Engineer, Carom Onesti

ROSEMOUNT®

For more information:
www.rosemount.com


EMERSON™
Process Management

This unreliability meant that it was not possible to adjust the delivery of steam in response to the user's requests. As well as losing operational efficiency, the clear need to apply optimization technologies on the boilers was limited by the lack of precise measurements. To resolve these issues, Carom needed to replace the orifice plate flowmeters with the best technology for superheated steam measurement.

SOLUTION

Following discussions with engineers from Emerson, Romania, CAROM installed three Rosemount® 8800D Vortex flowmeters with integral temperature sensors in each line. The flowmeters were installed with Rosemount pressure transmitters and a flow computer. The Rosemount 8800D vortex flowmeter was chosen due to its all cast body - this results in improved plant safety, process availability and efficiency, and measurement reliability. Emerson's innovative design features flow and temperature sensors located outside the process - enabling maintenance without stopping the process.

Following installation, the improvements were immediately evident and after one year of use the results have been quantified by CAROM. For example, the steam losses around 1 - 1.5 tonnes per hour have been eliminated and this has improved the steam system efficiency by 3%. Based on the current cost of fuel this equates to a saving of more than 200,000 Euros per year. Using these savings, the initial investment was recovered in just 25 days of operation.

Based on these impressive results, Carom is planning to install additional Vortex flowmeters to further optimize their distribution system. Carom is also planning the implementation of Emerson's Vortex technologies for new projects including one new (C4 fraction) hydrogenation plant.

RESOURCES

Rosemount Vortex Flowmeters

<http://www2.emersonprocess.com/en-US/brands/rosemount/Flow/Vortex-Flowmeters/Pages/index.aspx>

The Emerson logo is a trade mark and service mark of Emerson Electric Co. Rosemount and the Rosemount logotype are registered trademarks of Rosemount Inc. All other marks are the property of their respective owners.

Standard Terms and Conditions of Sale can be found at www.rosemount.com/terms_of_sale

Emerson Process Management
Rosemount Division
8200 Market Boulevard
Chanhassen, MN 55317 USA
T (U.S.) 1-800-999-9307
T (International) (952) 906-8888
F (952) 906-8889
www.rosemount.com

Emerson Process Management Flow B.V.
Neonstraat 1
6718 WX Ede
The Netherlands
Tel +31 (0) 318 495555
Fax +31 (0) 318 495556

Emerson Process Management
Emerson Process Management Asia Pacific
Private Limited
1 Pandan Crescent
Singapore 128461
T (65) 6777 8211
F (65) 6777 0947
Enquiries@AP.EmersonProcess.com

Emerson FZE
P.O. Box 17033
Jebel Ali Free Zone
Dubai UAE
Tel +971 4 811 8100
Fax +971 4 886 5465

Emerson Process Management Latin America
Multipark Office Center
Turrubares Building, 3rd and 4th Floor
Guachipelin de Escazu, Costa Rica
Tel +(506) 2505-6962
International.mmicam@emersonprocess.com

ROSEMOUNT®

For more information:
www.rosemount.com

"Emerson's Vortex technology has enabled fuel savings of more than 200.000 Euros per year allowing our total investment to be recovered in just 25 days of operation."

Marian Stancu

*Energy Chief Engineer, Carom
Onesti*



EMERSON™
Process Management