



Revision Date: 06/19/2008

Issue date: 06/19/2008

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: 63/37 C400 2C 0.81MM 0.5KG AM (0.032)	Item No. : MM00986 / IDH No. 386825
Product type: Solder Wire	Region: United States
Company address: Henkel Corporation 15051 East Don Julian Road Industry, California 91746	Contact Information: Telephone: 626.988.6511 Emergency Telephone: 860.571.5100 Internet: www.electronics.henkel.us

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Tin 7440-31-5	60-100	2 mg/m ³ TWA 2 mg/m ³ TWA except Tin hydride	2 mg/m ³ TWA as Sn 2 mg/m ³ TWA	None
Lead 7439-92-1	30-60	0.05 mg/m ³ TWA	30 µg/m ³ Action Level as Pb. Poison - see 29 CFR 1910.1025 50 µg/m ³ TWA as Pb 50 µg/m ³ PEL as Pb	None
Modified rosin	1-5	None	None	None
Modified Resin Proprietary	1-5	None	None	None
Adipic acid 124-04-9	0.1-1	5 mg/m ³ TWA	None	None

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: Paste	HEALTH: 3*
Color: Grey	FLAMMABILITY: 1
Odor: Mild	PHYSICAL HAZARD: 0
	Personal Protection: See Section 8

DANGER: HARMFUL IF SWALLOWED, ABSORBED THROUGH SKIN OR INHALED.
POSSIBLE CANCER HAZARD.

Relevant routes of exposure: Skin, Inhalation, Ingestion

Potential Health Effects

Inhalation: Fumes and/or dust produced by this product may be hazardous in case of ingestion or inhalation. Rosin thermal decomposition product (as formaldehyde) is classified by NIOSH as a potential occupational carcinogen. Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's content to toxic levels. Fumes may be irritating or cause sensitization to the respiratory system. Excessive inhalation of fumes from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms) which come on a few hours after large exposures.

Skin contact: Harmful if absorbed through skin. Prolonged or repeated skin contact may cause irritation, skin sensitization and argyria (a non-toxic, cosmetic blue-gray discoloration of the skin and mucous membranes that is irreversible).

Eye contact: Contact with eyes will cause irritation.

Ingestion: Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's content to toxic levels. Symptoms of lead poisoning include abdominal pain, nausea, vomiting, and headache. May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by exposure:

Repeated or prolonged exposure to lead and its compounds may produce general health deterioration by an accumulation in one or more human organs.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If discomfort persists seek medical attention.

Skin contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. If a person feels unwell or symptoms of skin irritation appear, consult a physician.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

Ingestion: Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Flash point: 124°C (255°F)

Autoignition temperature: 202°C (396°F)

Flammable/Explosive limits-lower %: Not applicable

Flammable/Explosive limits-upper %: Not applicable

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Fire fighters should wear positive pressure breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gases.

Hazardous combustion products: Oxides of Metals in Section 2. The flux medium will give rise to irritating fumes. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Do not let product enter drains.

Clean-up methods: Scrape up spilled material and place in sealed container for disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with molten material. Avoid contact with eyes, skin and clothing. Do not wear contact lenses. Wash thoroughly after handling.

Storage: Store in original container until ready to use.

Incompatible products: Oxidizing agents. Strong acids or bases.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Ensure adequate ventilation, especially in confined areas.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

Eyeface protection: Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Grey
Odor:	Mild
Vapor pressure:	negligible vapor pressure at ambient temperatures
pH:	Not applicable
Boiling point/range:	Not determined
Melting point/range:	183°C (361°F) (solder alloy)
Specific gravity:	8.4
Vapor density:	Not applicable
Evaporation rate:	Not available
Solubility in water:	Insoluble.
Partition coefficient (n-octanol/water):	Not determined
VOC content:	Zero

10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors. Formaldehyde.
Incompatibility:	Incompatible with oxidising agents.
Conditions to avoid:	Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Tin 7440-31-5	No	No	No
Lead 7439-92-1	Suspect Carcinogen	Group 2B	Yes
Modified rosin	No	No	No
Modified Resin Proprietary	No	No	No
Adipic acid 124-04-9	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Tin 7440-31-5	Nervous System, Lung, Liver, Kidney, Irritant, Gastrointestinal
Lead 7439-92-1	Thyroid, Some evidence of carcinogenicity, Skin, Reproductive, Nervous System, Muscle, Liver, Kidney, Gastrointestinal, Eyes, Developmental, Blood, Behavioral
Modified rosin	No data
Modified Resin Proprietary	No Records
Adipic acid 124-04-9	Irritant, Kidney, Liver, Nervous System, Respiratory

12. ECOLOGICAL INFORMATION

Ecological Information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with Federal, State and local regulations. Do not dispose of in an uncontrolled manner.

EPA hazardous waste number: D008 Lead

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
DOT reportable quantity (lbs):	Adipic acid (CAS# 124-04-9) is reportable at 5000 lbs (2270 Kg)

International Air Transportation (ICAO/IATA):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information


TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None above reporting de minimus.
CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Lead (CAS# 7439-92-1).

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B



16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 1.3.4.6.8.10.14.15

Prepared by:

Lou Fabrizio, Senior Health & Regulatory Affairs Specialist
For Safety and Regulatory Information contact:
Product Safety and Regulatory Affairs,
Rocky Hill, CT.
860-571-5204

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

