Lower Berkeley County solves coating issues in primary sludge line with electrode coating diagnostic

RESULTS

- Eliminated meter failures
- Reduced operation and maintenance costs
- Reduced down time for maintenance and cleaning



APPLICATION

Wastewater treatment plant primary sludge transfer measurement

CUSTOMER

Berkeley County Water & Sanitation; Lower Berkeley Wastewater Treatment Plant, Goose Creek, SC

CHALLENGE

The Plant Electrical Maintenance Manager for the Lower Berkeley County Wastewater Treatment facility had problems with primary sludge coating the electrodes in the sensor causing the meter to fail. The process had to be shut down, the tube removed, cleaned and placed back in-line causing significant downtime and added maintenance costs. This was happening about every three months and they had to be reactive in their maintenance response because they never knew when the unit would fail.

Lower Berkeley Wastewater Treatment Plant primary sludge contained grease from industrial wastewater discharge which mixed with the sludge and formed a material that was coating the electrodes and solidifying to a paper mache-like consistency.

Because the amount of coating varied due to several factors, the amount of grease in the media and temperature, there was no way of knowing how much material was building up on the electrodes. The operators had to wait until there was a failure before they could service the meter. The line had to be shut down and the meter removed causing disruptions in operation. Maintenance schedules were also disrupted because personnel had to be pulled from routine maintenance to address the meter failures.

"The Rosemount magnetic flowmeter electrode coating diagnostic allows us to monitor the coating of the electrodes and warns us so we can clean the unit before a failure."

Steve Wolfensberger, Electrical Maintenance Manager





For more information: www.rosemount.com



SOLUTION

Rosemount 8750WA Magnetic Flowmeter solved the problem of electrode coating. The 8750WA tube was replaced with a tube using bullet-nose electrodes. A transmitter with the electrode coating diagnostic was installed. The diagnostic monitors the electrode resistance value changes caused by build-up on the electrodes. By determining the electrode resistance value just prior to a failure, the meter was set to warn the operator before that value is reached.

Advance warning of a pending failure gives the operators the ability to schedule maintenance and service the meter before a failure occurs, thus eliminating down-time and reducing maintenance headaches.

RESOURCES

Rosemount Magnetic Flowmeters

http://www2.emersonprocess.com/en-US/brands/rosemount/Flow/Magnetic-Flowmeters/Pages/index.aspx

Rosemount 8750WA Magnetic Flowmeter

http://www2.emersonprocess.com/siteadmincenter/PM%20Rosemount%20Documents/00813-0100-4750.pdf

"Between switching to bullet electrodes, flushing the system and the coating diagnostic we have not had a failure since."



Installed Rosemount 8750WA Magnetic Flowmeter

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which can be found at www.rosemount.com/terms_of_sale. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

The Emerson logo is a trade mark and service mark of Emerson Electric Co.
Rosemount and the Rosemount logotype are registered trademarks of Rosemount Inc.
PlantWeb is a registered trademark of one of the Emerson Process Management group of companies.
All other marks are the property of their respective owners.

Emerson Process Management

Rosemount Division 8200 Market Boulevard Chanhassen, MN 55317 USA T (U.S.) 1-800-999-9307 T (International) (952) 906-8888 F (952) 906-8889

www.rosemount.com

Emerson Process Management Latin America 1300 Concord Terrace, Suite 400, Sunrise, Florida 33323 USA Tel + 1 954 846 5030

Emerson Process Management

Blegistrasse 23 P.O. Box 1046 CH 6341 Baar Switzerland Tel +41 (0) 41 768 6111 Fax +41 (0) 41 768 6300

Emerson FZE

P.O. Box 17033 Jebel Ali Free Zone Dubai UAE Tel +971 4 811 8100 Fax +971 4 886 5465

Emerson Process Management

Emerson Process Management Asia Pacific Private Limited 1 Pandan Crescent Singapore 128461 T (65) 6777 8211 F (65) 6777 0947 Enquiries@AP.EmersonProcess.com



For more information: www.rosemount.com

