# Leading Gas Producer Decreases Operating and Capital Costs with Rosemount™ Conditioning Orifice Technology

# **RESULTS**

- Decreased operating costs with reduced flowline lengths
- Reduced environmental impact
- Improved field allocation with industry leading wet gas measurement



# **APPLICATION**

Gas flow allocation measurement in gas fields

# **CUSTOMER**

Leading gas producer in North America

# **CHALLENGE**

A leading gas producer operating over 2,000 wells in the western United States was looking for a gas flow meter that was less susceptible to errors from varying amounts of produced liquids (wet gas). High accuracy was needed for these wells for allocation measurements. The operator was using a traditional orifice plate which was causing inaccuracies in the gas flow measurement, resulting in unreliable data and high field allocation factors.

The only other option that the producer was aware of was to place a separator at each well so that an accurate gas flow rate could be determined. This option would have made a large environmental impact and resulted in high capital costs.

To solve this problem of high capital costs and environmental sensitivity, a flow meter needs to be installed in the pipe before it reaches the header and be accurate with minimum straight run.

This producer has standardized on the Rosemount Conditioning Orifice Plate, enabling them to better determine overall well performance and improved field measurement with reduced capital costs and environmental impact.





# SOLUTION

Emerson<sup>™</sup> proposed the Rosemount Conditioning Orifice Plate in place of the traditional orifice plate to accommodate a short meter run and handle produced liquids. This solution eliminated the separator and flowline lengths, decreasing capital costs while reducing environmental impact.

To handle the liquids, the Rosemount Conditioning Orifice Plate was positioned with one of the four holes on the bottom of the pipe, which allowed any free liquids to continue flowing and cause minimal damming effect. The Rosemount Conditioning Orifice Plate utilizes a four-hole design and advanced orifice technology to improve accuracy while reducing the requirements for upstream straight piping to two pipe diameters downstream of most disturbances.



Rosemount Conditioning Orifice Plate

This producer has standardized on the Rosemount Conditioning Orifice Plate, enabling them to better determine overall well performance and improve field measurement while reducing capital costs and environmental impact.

# **RESOURCES**

Rosemount Oil & Gas Instrumentation

Emerson.com/Industries/Oil-Gas

**Rosemount 1595 Conditioning Orifice Plate** 

Emerson.com/Rosemount/Rosemount-1595-Conditioning-Orifice-Plate

Emerson Terms and Conditions of Sale are available upon request. The Emerson logo is a trademark and service mark of Emerson Electric Co. Rosemount is a mark of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2018 Emerson. All rights reserved.

# **Global Headquarters**

# **Emerson Automation Solutions**

6021 Innovation Blvd. Shakopee, MN 55379, USA

+1 800 999 9307 or +1 952 906 8888

+1 952 949 7001

RFQ.RMD-RCC@Emerson.com

#### **Europe Region**

# **Emerson Automation Solutions** Europe GmbH

Neuhofstrasse 19a P.O. Box 1046 CH 6340 Baar, Switzerland

+41 (0) 41 768 6111

+41 (0) 41 768 6300

RFQ.RMD-RCC@Emerson.com

in Linkedin.com/company/Emerson-Automation-Solutions

Twitter.com/Rosemount\_News

Facebook.com/Rosemount

Youtube.com/user/RosemountMeasurement

☑ Google.com/+RosemountMeasurement

#### Middle East and Africa Region **Emerson Automation Solutions**

Emerson FZE P.O. Box 17033. lebel Ali Free Zone - South 2 Dubai, United Arab Emirates

+971 4 8118100

+971 4 8865465

RFQ.RMTMEA@Emerson.com

# **Asia Pacific Region Emerson Automation Solutions**

1 Pandan Crescent Singapore 128461

+65 6777 8211

+65 6777 0947

Enquiries@AP.Emerson.com

00830-0600-4828, Rev BA

