

# Pulp and Paper Supplier Improves Paper Quality with High Process Noise Diagnostic

## RESULTS

- Reduced risk of decreased paper strength
- Decreased waste
- Decreased operations cost



## APPLICATION

Pulp stock flow after LCR refiner

## CUSTOMER

Leading global supplier of pulp and paper products

## CHALLENGE

This pulp and paper supplier uses a magnetic flow meter to measure the total flow of pulp stock after several LCR refiners. LCR refiners buff or curl the pulp fibers to help bond the fibers together creating a much stronger paper. This customer was having difficulty providing a uniform flow of the stock through the refiner blades and a continuous uniform fiber supply to the paper machine.

The source of the problem was due to an unstable flow measurement from the installed magnetic flow meter. The unstable measurement required that the loop be run in manual mode in order to maintain the correct paper strength.

Due to the unstable measurement, this customer risked decreased paper strength and reduced quality. In order to ensure product quality was met, target set points could not be optimized increasing waste. Increased operation costs were incurred while the loop remained in manual mode.

## SOLUTION

Due to the critical nature of this measurement, it was decided to upgrade the remote transmitter to a Rosemount 8700 Magnetic flowmeter system transmitter. As soon as the new transmitter was connected to the sensor, a High Process Noise diagnostic alert

*8700 Magnetic flowmeter system high process noise diagnostic and selectable coil drive frequency restores automatic control and improves paper quality.*

**ROSEMOUNT**<sup>®</sup>

For more information:  
[www.rosemount.com](http://www.rosemount.com)

  
**EMERSON**<sup>™</sup>  
Process Management

appeared on the display. The transmitter displayed the signal to noise ratios at both 5 and 37 Hz. The signal to noise ratio at 5 Hz was below the recommended limit for a stable flow measurement. Based on this information, the technician switched coil drive frequency to 37 Hz. The 37 Hz coil drive frequency had a much higher signal to noise ratio and the measurement immediately stabilized.

Rosemount's High Process Noise Diagnostic and user selectable coil drive frequency improved the stability of the measurement allowing the mill to run in automatic mode decreasing operation costs. With the ability to more tightly control the process, waste was reduced. The improved control also ultimately resulted in consistently higher paper strength ensuring the highest quality paper product.

## RESOURCES

### Emerson Process Management Pulp & Paper Industry

<http://www2.emersonprocess.com/en-US/plantweb/customerproven/Pages/PulpPaper.aspx>

### Rosemount 8700 Magnetic Flowmeters

<http://www2.emersonprocess.com/en-US/brands/rosemount/Flow/Magnetic-Flowmeters/Pages/index.aspx>

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which can be found at [www.rosemount.com/terms\\_of\\_sale](http://www.rosemount.com/terms_of_sale). We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

The Emerson logo is a trade mark and service mark of Emerson Electric Co. Rosemount and the Rosemount logotype are registered trademarks of Rosemount Inc. PlantWeb is a registered trademark of one of the Emerson Process Management group of companies. All other marks are the property of their respective owners.

#### Emerson Process Management

**Rosemount Incorporated**  
8200 Market Boulevard  
Chanhassen, MN 55317 USA  
[www.rosemount.com](http://www.rosemount.com)  
Tel (USA) +1 800 522 6277  
Tel (International) +1 (303) 527 5200  
Fax +1 (303) 530 8459

#### Emerson Process Management

Blegistrasse 23  
P.O. Box 1046  
CH 6341 Baar  
Switzerland  
Tel +41 (0) 41 768 6111  
Fax +41 (0) 41 768 6300

#### Emerson FZE

P.O. Box 17033  
Jebel Ali Free Zone  
Dubai UAE  
Tel +971 4 811 8100  
Fax +971 4 886 5465

#### Emerson Process Management Asia Pacific Private Limited

1 Pandan Crescent  
Singapore 128461  
T (65) 6777 8211  
F (65) 6777 0947  
[Enquiries@AP.EmersonProcess.com](mailto:Enquiries@AP.EmersonProcess.com)

#### Emerson Process Management Latin America

**Multipark Office Center**  
Multipark Office Center  
Turrubares Building, 3rd & 4th floor  
Guachipelin de Escazu, Costa Rica  
T+(506) 2505-6962  
[international.mmicam@emersonprocess.com](mailto:international.mmicam@emersonprocess.com)

**ROSEMOUNT**<sup>®</sup>

For more information:  
[www.rosemount.com](http://www.rosemount.com)



**EMERSON**<sup>™</sup>  
Process Management